

Specifications

Model		Z700										
		Z723KH-2-48	Z724KH-2-54	Z725KH-2-60	Z724XKW-2-48	Z724XKW-2-54	Z726XKW-2-60	Z751KWi-48	Z781KWi-54	Z781KWTi-60		
Engine	Kubota Model Number	GH680V	GH730V	GH740V	GH735V	GH860V	GH7303V-F	GH860V-F				
	Engine manufacture	KOHLER®			Kawasaki®							
	Type	Gasoline, air-cooled V-Twin										
	Max. engine power	HP	22.5***	23.5***	25***	23.5**	25.5**	29.5**				
	Engine displacement	cu. in. (cc)	42.3 (694)	45.6 (747)		44.2 (726)	52.0 (852)	44.3 (726)	52.0 (852)			
	Starting system	Key switch										
Dimensions	Overall length	in. (mm)	83.9 (2131)									
	Overall width	(w/ mower)	in. (mm)	61.3 (1557)	67.3 (1709)	73.8 (1875)	61.3 (1557)	67.3 (1709)	73.8 (1875)	61.3 (1557)	67.3 (1709)	73.8 (1875)
		(w/o mower)	in. (mm)	50.4 (1280)		54.7 (1389)	50.4 (1280)		54.7 (1389)	50.4 (1280)		54.7 (1389)
	Overall height	(w/ ROPS upright)	in. (mm)	70.1 (1780)								
		(w/ ROPS folded)	in. (mm)	48.6 (1235)								
Wheelbase		in. (mm)	50.9 (1293)									
Tread	Front	in. (mm)	37.6 (954)									
	Rear	in. (mm)	40.2 (1021)		42.6 (1082)	40.2 (1021)		42.6 (1082)	40.2 (1020)		42.7 (1085)	
Tire size	Front		13 x 5.0 – 6 (Flat Free)		13 x 6.5 – 6 (Flat Free)	13 x 5.0 – 6 (Flat Free)		13 x 6.5 – 6 (Flat Free)				
	Rear		24 x 9.5 – 12		24 x 12 – 12	24 x 9.5 – 12		24 x 12 – 12	24 x 9.5 – 14		24 x 12 – 14	
Weight (w/ mower deck)		lbs. (kg)	1168 (530)	1182 (536)	1213 (550)	1186 (538)	1195 (542)	1235 (560)	1215 (551)	1254 (569)	1285 (583)	
Transmission			Parker®**** HTG14 Transmissions									
Transmission system			2 HST-2 G rotor type									
Speed control			2 hand levers									
Traveling speed range	Forward	mph (km/h)	0–11.2 (0–18)									
	Reverse	mph (km/h)	0–5.6 (0–9.0)									
Brake type			Drum disks, foot applied, released									
PTO system	Type		Belt drive									
	Clutch type		Electromagnetic clutch									
	PTO brake		Dry disc									
Mower deck	Model		RCK48P-723Z	RCK54P-724Z	RCK60P-725Z	RCK48P-723Z	RCK54P-724Z	RCK60P-725Z	RCK48P-751Z	RCK54P-781Z	RCK60P-781Z	
	Cutting width	in.	48 (1219)	54 (1372)	60 (1524)	48 (1219)	54 (1372)	60 (1524)	48 (1219)	54 (1372)	60 (1524)	
	Mower lift system		Mechanical									
	Mower deck type		Commercial fabricated deck									
	Deck depth	in. (mm)	6.0 (152.4)									
	Belt type		Single belt									
	Deck steel thickness	Ga (mm)	8 (4.18)									
	Anti-scalp roller		Rigid									
	Number of blades		3									
	Mounting method		Parallel linkage									
	Cutting height	in. (mm)	1.0 - 5.0 (25 - 127)						1.0 - 5.5 (25 - 140)			
	Blade tip speed (max.)	FPM	18600						18400	18600		
	Parking brake		Foot pedal									
Seat			21.2" high back seat with "Premium Adjustable Suspension", 3" vertical and 6" front to back travel									
Fuel tank capacity		gals. (ltrs.)	11.6 (43.9)									
Engine stop system			Key stop									
Battery			U1 (12V, RC: 45min, CCA: 300, CA: 410)									
Generator capacity		Amp	15A									

** These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

*** Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

**** Parker® is a registered trademark of Parker Hannifin Corporation.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.